

tesamoll® UNIVERSAL foam

BNR 5412, 5428, 5452, 5454, 5456, 55604

tesamoll® Universal Foam is a versatile self-adhesive foam designed to save money by sealing windows and doors. It is a draught stopper for gaps up to 5 mm.

Features

- Self-adhesive foam profile
- Seals gaps from 1 to 5mm
- Durability from 1 to 2 years
- Soft and flexible

Product Properties

- | | | | |
|---------------------------|--------|----------------------|----------|
| • Applicationfield | Home | • Solvent free | yes |
| • Durability | 2 Year | • Batteries required | no |
| • Humidity resistant | no | • Gap coverage | 1 - 5 mm |
| • Resistance to chemicals | No | • Batteries included | no |

Technical Data

- | | | | |
|--------------------------|------------------|--------------------------------|--------|
| • Material | Stainless steel | • Temperature resistant | yes |
| • Residue-free removable | no | • Temperature resistance from | -20 °C |
| • Type of adhesive | synthetic rubber | • Temperature resistance up to | 60 °C |
| • Backing material | PVC film | | |

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=05412>