



tesa® Spray glue Permanent

BNR 60020, 60021

tesa® Spray Glue Permanent is a spray adhesive for large surfaces. It offers extra strong bonding for typical household materials such as paper or cardboard.

Features

- For clean, economical, secure and fast bonding of large areas
- Suitable for light and medium-weight materials with slightly uneven surfaces
- Finely and evenly dispersion of glue
- Fast drying
- Resistant to damp and temperature from -20°C up to +60°C
- Suitable for Styrofoam®
- Free from silicone

Product Properties

- | | | | |
|---------------------------|----------------------------------------------------|-------------------------------------------|-----|
| • Applicationfield | Office, Home | • Suitable for children of 3 years of age | no |
| • UV-resistant | yes | • Waterproof | yes |
| • Water resistant | yes | • Washable | no |
| • Humidity resistant | yes | • Recyclable | no |
| • Resistance to chemicals | Yes | • Compostable | no |
| • Solvent free | no | • Batteries required | no |
| • Suitable surfaces | Even wood, Fabrics,
Stone, Brick, Acrylic glass | • Batteries included | no |
| • Refillable | no | | |

Technical Data

- | | | | |
|-------------------------------|---------------|------------------------------------|-------|
| • Ecofriendly packaging | no | • Temperature resistance up to | 60 °C |
| • Residue-free removable | no | • Silicone free | yes |
| • Adhesive strength | High adhesion | • Hazard material | yes |
| • Temperature resistance from | -20 °C | • Recommended distance of spraying | 20 cm |

tesa[®] Spray glue Permanent

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=60020>