## **Product Information**



# tesapack® BASIC Packaging tape

### BNR 53390, 58570, 58571, 58572, 58573, 58574, 58575

The tesa® BASIC Packaging Tape makes sealing your boxes and cartons easy. The tape easily unwinds, is solvent-free and resistant to both UV light and aging. Thus, you can rely on it sticking to and securing your packages for a long time – whether you're shipping a package to a friend or perhaps back to an online shop.

#### Features

• Dimensions: 66m:50mm / 50m:45mm / 40m:45mm \* Solvent free \* UV- and age-resistance \* Easy unwinding

#### **Product Properties**

<ul> <li>Applicationfield</li> <li>Quality</li> <li>Transparency</li> <li>Tear resistant</li> <li>Writable</li> <li>Hand tearable</li> <li>Dispenser included</li> <li>Low noise unwinding</li> <li>Spare part service</li> </ul>	Office, Home Standard quality High transparency yes no no no no no	<ul> <li>Humidity resistant</li> <li>Solvent free</li> <li>Suitable surfaces</li> <li>Reusable</li> <li>Refillable</li> <li>Shape</li> <li>Batteries required</li> <li>Batteries included</li> </ul>	no yes Cardboard no Roll no no
Technical Data			
<ul> <li>Material</li> <li>Residue-free removable</li> <li>Adhesive strength</li> <li>Type of adhesive</li> <li>Backing material</li> <li>Tensile strength</li> </ul>	PP (polypropylene) no Light adhesion water-based acrylic BOPP 38 N/cm	<ul> <li>Total thickness</li> <li>Age-resistant</li> <li>Tensibility</li> <li>Max roll width</li> <li>Max roll length</li> </ul>	41 μm yes 147 % 50 mm 66

#### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

